

Product Specification

Base Oil	Synthetic
Colour	Black
Texture	Tacky
ASTM Penetration	min 170 in Bulk form min 80 in Stick form
Drop Point	None
Compatibility	Excellent
Solvent Resistance	Excellent
Special Additives	MOS ₂
Composition	Semi liquid to Stick Grade
Temperature Range	-20 °C to +350°C

Order Details
Ordering Size
Part No.

A Stick – 6.35 × 22.23 (mm) – 90/ Box	HT-650-90 A
B Stick – 10.32 × 34.93 (mm) – 48/ Box	HT-650-48 B
C Stick – 13.89 × 50.80 (mm) – 24/ Box	HT-650-24 C
D Stick – 16.67 × 73.02 (mm) – 24/ Box	HT-650-24 D
G Stick – 21.83 × 85.73 (mm) – 24/ Box	HT-650-24 G
J Stick – 37.31 × 222.25 (mm) – 4/Box	HT-650-4 J
J Stick – 37.31 × 222.25 (mm) – 6/Box	HT-650-6 J
J Stick – 37.31 × 222.25 (mm) – 12 /Box	HT-650-12 J
K Stick – 38.89 × 254.00 (mm) – 4/Box	HT-650-4 K
K Stick – 38.89 × 254.00 (mm) – 6/Box	HT-650-6 K
K Stick – 38.89 × 254.00 (mm) – 12 /Box	HT-650-12 K
4.5 Kg Tin	HT-650-4.5 Kg
18 Kg Pail	HT-650-18 Kg
250 gr. Tube	HT-650-0.3 T

RAGA HT-650 ماده آبیندی و روانکاری شیرآلات BALL-PLUG از نوع سنتیک بوده و قابلیت عمل تا درجه حرارت ۳۵۰ درجه سانتیگراد را دارا می باشد.

RAGA HT-650 برای استفاده در شیرآلات در تماس با گاز طبیعی، میعانات گازی و سایر فرآورده های سبک نفت خام بسیار مناسب بوده و طول عمر بالایی دارد.

RAGA HT-650 Valve Sealant has been specifically formulated to provide lubrication and Sealing for plug and Ball valves used in elevated temperature Service.

RAGA HT-650 is composed of Liquid and Solid Polymetric hydrocarbons Compounded with a Synthetic fluid to Provide thermal stability and oxidation resistance.

Raga HT-650 is Suitable for elevate temperature Services involving hot hydrocarbon gases and vapors, Water, Steam and aqueous solution.

