RAGA Valve Cleaner





Product Specification

Base oil	Synthetic
Colour	Black
ASTM Penetration	290-330 in Bulk form
Composition	Semi liquid
Temperature Range	-40 °C to +80°C

Order Details

Ordering Size	Part No.
4.5 Kg Tin	VC -4.5 Kg
18 Kg Pail	VC -18 Kg
250 gr. Tube	VC -0.3 T

این ماده برای شیرآلاتی که بر اثر رسوب گرفتگی، خشک شدن مواد روانکاری و آببندی قبلی، رسوبات ناشی از عبور جریان گاز یا نفت دچار گرفتگی و عدم سهولت در باز و بسته شدن، شده اند کاربرد دارد.

با تزریق این ماده توسط گریس پمپ های متداول تزریق مواد آببندی کلیه رسوبات مذکور حل شده و از داخل شیر خارج می شود.

تمیز کننده شیر برای کلیه شیرآلات کاربرد داشته و هیچ اثری بر روی قطعات لاستیکی شیر ندارد.

جهت استفاده از این ماده به دستورالعمل مربوطه مراجعه شود.

RAGA Valve Cleaner is a soft gel, combination of solvent and synthetic lubrication oils formulated to be injected directly into the seat sealant system to clean important seal faces and sealant passages. Cycle the valve (if permitted) to ensue complete coverage, to allow the valve cleaner to soften old sealants and remove residual build-up from seal points. The best results are achieved by displacing the valve cleaner with equal quantities of lubricant/ sealant after cleaning. RAGA Valve Cleaner is recommended for use in ball, gate or plug valves and orifice fitting, It's also safe for all types of Oring, elastomer, plastics and other polymer which are used in valves.